



04-HS 458158-EC1

CERTIFICATE NUMBER

Superior Products International

COMPANY

Shawnee, Kansas, USA

PLANT LOCATION

Houston, Texas, USA

PORT OFFICE

EC Type Examination Certificate

Notified Body 0729

Product Designation: Enamo Grip I & II

This is to certify that ABS Europe Ltd, as a Notified Body under the authorization of UK MCA by Merchant Shipping Equipment Regulation, SI 1999, No. 1957 and M Notice No. 1734, as amended, did undertake the relevant type examination procedure of the product listed and same was found to be in compliance with the provisions of these Regulations and EU Directive 96/98/EC of 20 December 1996 as amended by EU Directive 2002/75/EC of 2 September 2002

This certificate is issued in compliance with Conformity Assessment Module B of the Regulations and Directives listed above.



15 September 2004

ISSUE DATE

14 September 2009

EXPIRATION DATE

R.M. Bell

SIGNATURE

R.M. Bell



Certificate No.: 04-HS 458158-EC1

Entry Date: 15 September 2004

**Name of Equipment/
Component Manufacturer:** Superior Products International
10835 W. 78th Street
Shawnee
Kansas
66214
USA

Tel: +1-913-962-4848
Fax: +1-913-962-6767

Equipment/Component: Coatings

Model: Enamo grip, Enamo grip ii


Description: Two-part polyurethane enamel coating that performs as a hard, durable top coat on steel, concrete, masonry, wood, and most other surfaces. Made of a self-levelling formula, it provides exceptional adhesion, flexibility and abrasion/impact resistance as well as excellent colour retention and chalk resistance when used on exterior surfaces. Resistant to water and humidity, stains, chemicals and solvents. Protects against graffiti by allowing for easy removal. Enamo Grip II contains additional solids and has a lower level of VOCs than Enamo Grip. All other characteristics of these two variants are the same. See attached "pdf"

Intended Service: Bulkhead, ceilings and decks in marine applications where compliance with IMO requirements for smoke and toxicity and low surface flammability are indicated.

Ratings: Meets the SOLAS 1974 (as amended) requirements for paints/finish materials requiring compliance with Parts 2 (Smoke & Toxicity) and 5 (Surface Flammability) of the IMO FTP Code, Res.MSC.61(67).

Notified





Standards:

European Union Marine Equipment Directive
96/98/EC as Amended by 2002/75/EC

IMO Res.MSC.61(67) Parts 2 & 5, IMO
Res.A.653(16)

Service Restrictions:

- 1) General shipboard and offshore use.
- 2) This product may not be used solely in order to provide A-Class, B-Class or F-Class fire resistance to coated surfaces where such classification is required, unless further testing has been performed and approval has been achieved.
- 3) This product may not be used in applications requiring intumescent coatings.

Comments:

- 1) Coating thickness - Enamo Grip - 9 mils (wet), 5 mils (dry); Enamo Grip II - 7 mils (wet), 3.5 mils (dry).
- 2) Application and use are to be to the manufacturer's instructions and the limitations set forth herein.

Notified Body 0729





ABS

TYPE APPROVAL PROGRAM

04-CH 458158-MED1
CERTIFICATE NUMBER

Superior Products International
COMPANY

Shawnee, Kansas, USA
PLANT LOCATION

Chicago, USA
PORT OFFICE

ABS Quality Assessment Certificate

Notified Body 0729

Manufacturing Plant - Location: Shawnee, Kansas, USA

This is to certify that ABS Europe Ltd, as a Notified Body under the authorization of UK MCA by Merchant Shipping Equipment Regulation, SI 1999, No. 1957 and M Notice No. 1734, as amended, did undertake the relevant conformity assessment of the manufacturing plant listed and same was found to be in compliance with the provisions of these Regulations and EU Directive 96/98/EC of 20 December 1996 as amended by EU Directive 2002/75/EC of 2 September 2002

Reference should be made to EC Type Examination Certificate,
No: 04 HS 458158 EC1 Dated 15 September 2004

This certificate is issued in compliance with Conformity Assessment Module **D** of the Regulations and Directives listed above.



15 September 2004
ISSUE DATE

14 September 2009
EXPIRATION DATE

R.M. Bell
SIGNATURE R.M. Bell



Certificate No.: 04-HS 458158-MED1

Entry Date: 15 September 2004

**Name of Equipment/
Component Manufacturer:** Superior Products International
10835 W. 78th Street
Shawnee
Kansas
66214
USA

Tel: +1-913-962-4848
Fax: +1-913-962-6767

Equipment/Component: Coatings

Model: Enamo grip, Enamo grip ii

Description: Two-part polyurethane enamel coating that performs as a hard, durable top coat on steel, concrete, masonry, wood, and most other surfaces. Made of a self-levelling formula, it provides exceptional adhesion, flexibility and abrasion/impact resistance as well as excellent colour retention and chalk resistance when used on exterior surfaces. Resistant to water and humidity, stains, chemicals and solvents. Protects against graffiti by allowing for easy removal. Enamo Grip II contains additional solids and has a lower level of VOCs than Enamo Grip. All other characteristics of these two variants are the same. See attached "pdf"

Intended Service: Bulkhead, ceilings and decks in marine applications where compliance with IMO requirements for smoke and toxicity and low surface flammability are indicated.

Ratings: Meets the SOLAS 1974 (as amended) requirements for paints/finish materials requiring compliance with Parts 2 (Smoke & Toxicity) and 5 (Surface Flammability) of the IMO FTP Code, Res.MSC.61(67).

Notified



Standards:

European Union Marine Equipment Directive
96/98/EC as Amended by 2002/75/EC

IMO Res.MSC.61(67) Parts 2 & 5, IMO
Res.A.653(16)

The manufacturer is allowed to affix the U.S. Coast
Guard approval number 164.112/0729/458158-1 as
allowed by the "Agreement between the European
Community and the United States of America on
Mutual Recognition of Certificates of Conformity
for Marine Equipment" signed February 27th, 2004

Service Restrictions:

- 1) General shipboard and offshore use.
- 2) This product may not be used solely in order to
provide A-Class, B-Class or F-Class fire resistance to
coated surfaces where such classification is required,
unless further testing has been performed and
approval has been achieved.
- 3) This product may not be used in applications
requiring intumescent coatings.

Comments:

- 1) Coating thickness - Enamo Grip - 9 mils (wet), 5
mils (dry); Enamo Grip II - 7 mils (wet), 3.5 mils
(dry).
- 2) Application and use are to be to the
manufacturer's instructions and the limitations set
forth herein.

Notified Body 0729

